

# NEW



## gas spring "Click & Go"

### Only one push on the release button...

The new click & go gas spring is a very comfortable alternative for all applications where the lockable gas spring shall always be **pushed out completely** after the release process. Due to the new click & go gas spring, this is possible with a **single short push** on the button. A permanent release over the whole stroke of the gas spring isn't necessary anymore. After a

**single release**, the gas spring remains in released condition.

This gas spring type can, of course, be released by a hydraulic release system as well as by bowden wire. For further information about release systems and its respective connecting parts, please see our latest Bansbach-catalogue.

Facts:

- **size:** 8/28 or 10/28 mm
- **force F1:** up to 1300 N
- **stroke:** up to 700 mm

- CeramPro® **piston rod, very corrosion-resistant**

thread piston rod	connecting part cylinder	model	push-out speed	type	stroke	extended length (EL1)	progressivity ca %	Index No.*	extension force
<b>K0</b>	<b>L0</b>	<b>L</b>	-	<b>E</b>	<b>250</b>	<b>591</b>		<b>001*</b>	<b>200</b>
<b>K0 =</b> MF 10x1x18	see catalogue page 44	L	- normal <b>0</b> fast <b>K</b> = short release <small>Auslöseweg &lt; 1 mm</small>	<b>E</b> 8/28	10 - 300	stroke x 2 + 91	13	* With the index no. – only necessary for repeating orders – we can reproduce exactly the same gas spring which has already been produced. You will receive the index no. with the order confirmation/invoice.	40 - 700 N
<b>W0 =</b> MF 8x1x16				<b>3</b> 10/28	10 - 700	stroke x 2 + 99	21		50 - 1300 N

The flyer is subject to technical alterations and printing mistakes.

**Winco Easylift B.V.**  
Postbus 343  
7575 AH OLDENZAAL

Tel. + 31 (0) 541-520044  
Fax + 31 (0) 541-511293

info@winco-easylift.nl  
www.winco-easylift.nl

**wincoeasylift®**  
Gasveren. Oldenzaal